


INSTALLATION INSTRUCTIONS:


- A. PROVIDE 9¹/₄" X 24¹/₄" WALL OPENING AND BACKING (1) TO ACCEPT CABINET. MINIMUM 5¹/₂" DEPTH FROM FINISHED WALL.
- B. DRILL HOUSING (2) TO LOCATE MOUNTING POINTS WHERE BACKING EXISTS. REMOVE HOUSING (2) AND INSTALL WALL ANCHORS (3) (BY OTHERS) AS REQUIRED FOR WALL/TYPE BACKING.
- C. INSTALL FIRE EXTINGUISHER HOUSING (2) INTO WALL OPENING (1).
- D. FASTEN HOUSING (2) INTO WALL USING SCREWS TO SUIT WALL CONSTRUCTION (BY OTHERS).

IMPORTANT! AFTER INSTALLATION, ALL JOINTS REQUIRE SECURITY SEALANT BY INSTALLER TO ELIMINATE GAPS BETWEEN WALL AND FIXTURE.

LOCATE ITEM TO CONFORM WITH APPLICABLE CODES FOR ACCESSIBILITY.



NOTE:
WEIGHT WITHOUT FIRE EXTINGUISHER = 14 lbs.

 WHITEHALL MANUFACTURING P.O. BOX 3527 Industry, CA 91744 15125 Proctor Ave Industry, CA 91746 (626) 968-6661 FAX (626) 855-4862	TITLE LIGATURE RESISTANT RECESSED FIRE EXTINGUISHER CABINET WH1704-A		
	MANUFACTURE DATE AUGUST 2018 TO PRESENT	DATE ISSUED 10/12/2022	DRAWING NUMBER 9918-135-001