



## Whitehall Ligature Resistant Component Shower

Model WH538-FH-CSH-SRCH  
 Model WH538-FH-CSH-SRCH-WH1832-PF



WH538-FH-CSH-SRCH

US PATENTS - US 10,474,170 B2 & US D697,591

### Ligature Resistant Shower

**Shower** components are arranged to be installed onto finished wall and serviced through a removable panel.

**Shower heads** are chrome plated brass with a 14 gage type 304 stainless steel white mounting flange powder coated and provides a vandal and ligature resistant shower head with a conical shape. Spray pattern is a non-adjustable multi-stream style and provides a 1.5 GPM flow rate.

**The T/P Mixing Valve** automatically mixes hot and cold water to deliver blended water within a specific range. Mixing Valve meets the most stringent performance criteria for temperature and pressure changes, defined by ASSE 1016. Valve conforms with lead free requirements of NSF61, Section 9, 1997.

**Stainless Steel Recessed Soap Dish for install into wall** is optionally available. Refer to WH1832-PF Series Submittal for additional Technical Data.

### GUIDE SPECIFICATION

Provide and install an Best-Care™ Ligature Resistant Component Shower. Exposed trim shall be chrome plated. Fixture shall be furnished with two Conical showerheads, an ASSE 1016 compliant control valve and diverter valve with Patented ADA Compliant Ligature Resistant Tri-Lever Handles.

### INSTALLATION NOTE:

*When components are installed properly they meet ADA requirements. Refer to local codes for any additional installation requirements. ADA compliance is subject to the interpretation and requirements of the Local Code Authority.*

Please visit [www.whitehallmfg.com](http://www.whitehallmfg.com) for most current specifications.



Complies with the following standards:



ASSE 1016  
 CSA B125.16






**MODEL NUMBER AND OPTIONS SELECTION:**

**BASE MODEL NUMBER**

- WH538-FH-CSH-SRCH                      Ligature Resistant Component Wall Shower
- WH538-FH-CSH-SRCH-WH1832-PF      Ligature Resistant Component Wall Shower with Recessed Soap Dish



**WH538-FH-CSH-SRCH**

- 1. UPPER -CSH CONICAL SHOWERHEAD.
- 2. -FH-CSH FIXED CONICAL SHOWERHEAD.
- 3. DIVERTER VALVE WITH PATENTED ADA COMPLIANT LIGATURE RESISTANT TRI-LEVER HANDLE.
- 4. T/P TEMPERATURE-PRESSURE BALANCING MIXING VALVE WITH ADA COMPLIANT LIGATURE RESISTANT TRI-LEVER HANDLE.

**DISCLAIMER:**

This product is designed to decrease the probability that it may be utilized as an apparatus for ligature. It is not a replacement for professionals who are trained in the proper evaluation, management and supervision of persons at risk of suicide.

**⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

**SELECTION SUMMARY & APPROVAL FOR MANUFACTURING**

Model Number & Options \_\_\_\_\_ Quantity \_\_\_\_\_  
 Company \_\_\_\_\_ Date \_\_\_\_\_  
 Contact \_\_\_\_\_ Title \_\_\_\_\_  
 Approval for Manufacturing/Signature \_\_\_\_\_

All dimensions are nominal and subject to manufacturer's change without notice. Whitehall assumes no responsibility for use of void or superseded data © Whitehall Manufacturing, Member of Morris Group International. Please visit [www.whitehallmfg.com](http://www.whitehallmfg.com) for most current specifications.