



Whitehall Manufacturing®
Manufacturer of Healthcare and Rehabilitation Products since 1946

Podiatry Whirlpools

Division of
Acorn Engineering Company®



A MEMBER OF



Use



P Series 10 Gallon Mobile Whirlpool

**P-10-M, P-10-MH,
P-10-MU**



P-10-MH

Whitehall P-10-M Mobile Whirlpools are recommended to facilitate hydrotherapy of the foot and ankle area, and when provided with a raised undercarriage, may also be used on the upper extremities.

Tank Capacity is 10 gallons.

P-10-MH is a Mobile Whirlpool with Handle of heavy duty construction with the hand grip section approximately 36" above ground level for ease in maneuvering the whirlpool from one location to another.

P-10-MU is a Mobile Whirlpool with Undercarriage of heavy duty construction and fixed height which raises the tank for use on the upper extremities.

Whirlpool Tank is 22"L x 13"W x 12"D and is seamless welded construction, fabricated from heavy gauge, type 304 stainless steel, polished to a satin finish. Tank rim is reinforced with a concealed stainless steel rod. Tank bottom is a seamless, coved (rounded) design for effective cleaning.

Heavy Duty Swivel Casters support all mobile models. Rear pair of casters are lockable for stabilizing during Whirlpool use.

Turbine Raising and Lowering Device permits adjustment of desired height and direction of water agitation towards the area of the body during whirlpool use. It is spring balanced and provided with a locking device.

Turbine Assembly functions both as agitator and emptying device. It is equipped with Underwriters Laboratory listed 1/2 HP jet pump motor protected with an ABS plastic shell, automatic thermal overload protector, and lifetime-sealed bearings. All parts contacting the water are stainless steel, chrome plated brass or bronze.

Drain option -SDP has a bottom drain, leading to a separate, concealed water evacuation pump. A hose is attached to the side of the unit during Whirlpool use to facilitate the evacuation.

Thermometer is provided with a dual scale, adjustable calibration, and a stem inserts into a retainer to prevent rattle during whirlpool agitation.

GUIDE SPECIFICATIONS

Provide Whitehall Mobile Whirlpool (specify model number and options) with a 10-gallon capacity, 22"L x 13"W x 12"D. Whirlpool shall be fabricated from heavy gauge, type 304 stainless steel. Construction shall be seamless welded and exposed surfaces shall be polished to satin finish. Bottom of tank shall be a seamless, rounded coved design. Whirlpool shall have heavy duty swivel casters with locking device on rear pair of casters. Provide a turbine assembly with raising and lowering device which functions both as agitator and emptying device, permits adjustment of desired height, direction of water agitation, and can be locked into place. Turbine assembly shall be UL listed 1/2 HP jet pump motor with automatic thermal overload protector and lifetime-sealed bearings. Provide a thermometer with a stem retainer to prevent rattling when whirlpool is in operation.

Please visit www.whitehallmfg.com
for most current specifications.



Whitehall Mfg. • P.O. Box 3527 • City of Industry, CA 91744 • (800) 591-9280 • (626) 968-6681

P-10-M

REV: 07/02/2024



MODEL NUMBER AND OPTION SELECTIONS

Series

P Podiatry Series

Capacity

10 Gallons

Type

- M Mobile Whirlpool
- M-MH Mobile Whirlpool with Handle
- M-MU Mobile Whirlpool with Undercarriage

Turbine Electrical Requirements

- 115VAC / 50Hz 115VAC / 60Hz
- 230VAC / 50Hz 230VAC / 60Hz

Country of Use _____

For Mixing Valve:

Refer to supplemental MXT15-OTG and DU-1 sheet for details.

Suffix Options (See Whirlpool Options Section for Details)

- ADH Auxiliary Drain Hose Assembly
- EG Enviro-Glaze® Color Powder Coating - Specify Color: _____
<https://www.whitehallmfg.com/enviro-glaze>
- GFI Ground Fault Interrupter
- HL Hydro Lift (Refer To Page HL)
- LOGO Applied Logos: Team, Facility, Company Logo
- SDP Separate Drain Pump

ELECTRIC REQUIREMENTS: Amps: 6.9/6.2 Hertz: 50/60 Volts: 115 GFI Receptacle	ELECTRIC REQUIREMENTS: Amps: 3.5/3.1 Hertz: 50/60 Volts: 230 GFI Receptacle	Certified per US & Canadian Medical Standards; UL 60601-1 & CSA C22.2 No. 601.1	Certified per European Standards; IEC 60601-1
--	--	---	---

Intertek
 5016885

MODEL P-10-M

MODEL P-10-MU

MOBILE P-10-M SERIES WHIRLPOOLS

NOTES:

1. 1/2 hp Jet Pump Motor	5. Auxiliary Drain Valve
2. Variable Pressure Control	6. Turbine Raising & Lowering Device
3. Thermometer	7. Optional -MU Undercarriage
4. Stainless Steel Tank	

All dimensions are nominal and subject to manufacturer's change without notice. Whitehall assumes no responsibility for use of void or superseded data © Whitehall Manufacturing, Member of Morris Group International. Please visit www.whitehallmfg.com for most current specifications.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING

Model Number & Options _____ Quantity _____

Company _____ Date _____

Contact _____ Title _____

Approval for Manufacturing/Signature _____